SUMMIT®
OPEN LUXURY FIREPLACES

Scan QR Code for installation and operation manual

48" SUMMIT OPEN LINEAR LUXURY FIREPLACE

UNIT PHYSICAL DIMENSIONS

Front Width: 54"

Height: 46 ¾"

Depth: 22"

BTUs:
SML-48BR-VEN (NG): 40,000 – 60,000
SML-48BR-VEP (LP): 30,000 – 60,000
SML-48BRT-VEN (NG): 45,000 – 69,000
SML-48BRT-VEP (LP): 30,000 – 62,000

FRONT PHYSICAL DIMENSIONS



TOP VIEW

SIDE ELEVATION



FRONT ELEVATION



REAR ELEVATION



FIREPLACE BURNER OPTIONS

BEDROCK CONTEMPORARY

Must add ½" reflective glass or lava granules (5 lbs/foot)

— *Optional*
6" Cannonballs in black, gray, or white
48" Western Driftwood Linear Log Set, 9 pieces

BEDROCK TRADITIONAL WITH GLOWFIRE™ LOGS

Must add ½" reflective glass or lava granules (5 lbs/foot)
Driftwood GlowFire™ logs included.

FIREPLACE PANELS

3/8" TEMPERED BLACK GLASS

BLACK MATTE

BLACK FLUTED FIBER

OFFSET BLACK FIBER BRICK


STACKED GRAY FIBER BRICK

VIEWING REDUCTION KIT

Viewing reduction kits are available as an add-on to reduce the viewing area by 6" in height, from 24" to 18" high. The kit includes the firebox reduction panel and side drywall stops.

**If installing as a corner view or bay corner(s), corner view kits are required.*

OPTIONAL POWER VENT KIT

Power vent kits are available as an add-on to provide greater flexibility in fireplace placement and vent routing, while ensuring safe and efficient operation.

FRONT VIEW

FRAMING DIMENSIONS



Width: 54 3/8"	**Height:** 47"	**Depth:** 22"	**Weight:** 310 lbs
Bottom to Drywall Stop: 6 3/4"		**Viewing Area:** 50 1/2"	



LEFT VIEW

FRAMING DIMENSIONS

Reverse for right view



Width: 53"	**Height:** 47"	**Depth:** 22"	**Weight:** 310 lbs
Bottom to Drywall Stop: 6 3/4"		**Viewing Area:** 51"	



BAY VIEW

FRAMING DIMENSIONS



Width: 51 3/4"	**Height:** 47"	**Depth:** 22"	**Weight:** 310 lbs
Bottom to Drywall Stop: 6 3/4"		**Viewing Area:** 51 5/8"	



CORNER VIEW

FRAMING DIMENSIONS



Width: 54 3/8"	**Height:** 47"	**Wall to Wall:** 97 3/4"	**Weight:** 310 lbs
Bottom to Drywall Stop: 6 3/4"	**Viewing Area:** 50 1/2"	**Angle Length:** 69 1/8"	



MINIMUM CLEARANCE TO COMBUSTIBLES

Back and sides of fireplaces	0" minimum
Floor	0" minimum
Perpendicular wall to opening	19" minimum
Top of fireplace	0" or top of studs minimum
Chimney outer pipe surface	1" minimum

VENTING

12" B-Vent

***Minimum Height 14"**

***No more than two 45° offsets**

**Unless using power vent*

MANTEL CLEARANCES

A combustible mantle shelf may be installed a maximum of 8" (20.3 cm) from the wall.

A combustible mantle shelf may be installed at a minimum of 6" above the opening of the fireplace and a maximum of 8" from the wall.



REQUIREMENTS FOR TV INSTALLATION

You can safely place a TV above the Summit fireplace, but the required clearance will depend on the TV manufacturer's guidelines.

When installing a TV 18" above the opening of the fireplace a mantel for heat deflection is required. If installing a TV 18" or more above the opening please refer to the TV manufacturer's required clearances guideline.



PRODUCT CODES

USA	ANSI Z21.50.2019
CAN	CSA 2.22.2019

MAKEUP-AIR REQUIREMENTS

SUMMIT SIZE	CONFIGURATION	CFM
48"	Front View	276
48"	Corner View	393
48"	Bay View	499

The product information provided is not complete and is subject to change without notice.

To avoid the risk of fire and potential injury, product installation must adhere strictly to instructions contained in the Installation and Operation Manual.