



Scan QR Code for installation
and operation manual



72" SUMMIT OPEN LINEAR LUXURY FIREPLACE

UNIT PHYSICAL DIMENSIONS


Front Width: 78"

Height: 46 $\frac{3}{4}$ "

Depth: 22"


BTUs: SML-72BR-VEN (NG): 60,000 – 90,000
SML-72BR-VEP (LP): 50,000 – 90,000
SML-72BRT-VEN (NG): 60,000 – 95,000
SML-72BRT-VEP (LP): 40,000 – 85,000

FRONT PHYSICAL DIMENSIONS



FIREPLACE BURNER OPTIONS

BEDROCK CONTEMPORARY



Must add 1/2" reflective glass or lava granules (5 lbs/foot)

— Optional

6" Cannonballs in black, gray, or white

72" Western Driftwood Linear Log Set, 13 pieces


BEDROCK TRADITIONAL WITH GLOWFIRE™ LOGS




Must add 1/2" reflective glass or lava granules (5 lbs/foot)

Driftwood GlowFire™ logs included.


FIREPLACE PANELS



3/8" TEMPERED
BLACK GLASS




BLACK MATTE



BLACK FLUTED FIBER



OFFSET BLACK
FIBER BRICK



STACKED GRAY
FIBER BRICK

VIEWING REDUCTION KIT

Viewing reduction kits are available as an add-on to reduce the viewing area by 6" in height, from 24" to 18" high. The kit included the firebox reduction panel and side drywall stops.


**If installing as a corner view or bay corner(s), reduction kits are required.*

OPTIONAL POWER VENT KIT

Power vent kits are available as an add-on to provide greater flexibility in fireplace placement and vent routing, while ensuring safe and efficient operation.


FRONT VIEW

FRAMING DIMENSIONS



Width: 78 3/8" | **Height:** 47" | **Depth:** 22" | **Weight:** 395 lbs


Bottom to Drywall Stop: 6 3/4" | **Viewing Area:** 74 1/2"



LEFT VIEW


FRAMING DIMENSIONS

Reverse for right view




Width: 77" | **Height:** 47" | **Depth:** 22" | **Weight:** 395 lbs

Bottom to Drywall Stop: 6 3/4" | **Viewing Area:** 75"




BAY VIEW

FRAMING DIMENSIONS




Width: 75 3/4" | **Height:** 47" | **Depth:** 22" | **Weight:** 395 lbs

Bottom to Drywall Stop: 6 3/4" | **Viewing Area:** 75 5/8"




CORNER VIEW

FRAMING DIMENSIONS



Width: 78 3/8" | **Height:** 47" | **Wall to Wall:** 121 3/4" | **Weight:** 395 lbs

Bottom to Drywall Stop: 6 3/4" | **Viewing Area:** 74 1/2" | **Angle Length:** 85 1/8"



MINIMUM CLEARANCE TO COMBUSTIBLES

Back and sides of fireplaces	0" minimum
Floor	0" minimum
Perpendicular wall to opening	19" minimum
Top of fireplace	0" or top of studs minimum
Chimney outer pipe surface	1" minimum

VENTING

12" B-Vent

*Minimum Height 14"


*No more than two 45° offsets

*Unless using power vent

MANTEL CLEARANCES

A combustible mantle shelf may be installed a maximum of 8" (20.3 cm) from the wall.

A combustible mantle shelf may be installed at a minimum of 6" above the opening of the fireplace and a maximum of 12" from the wall.



REQUIREMENTS FOR TV INSTALLATION

You can safely place a TV above the Summit fireplace, but the required clearance will depend on the TV manufacturer's guidelines.

When installing a TV 18" above the opening of the fireplace a mantel for heat deflection is required. If installing a TV 18" or more above the opening please refer to the TV manufacturer's required clearances guideline.

PRODUCT CODES

USA	ANSI Z21.50.2019
CAN	CSA 2.22.2019

MAKEUP-AIR REQUIREMENTS

SUMMIT SIZE	CONFIGURATION	CFM
72"	Front View	404
72"	Corner View	518
72"	Bay View	633

The product information provided is not complete and is subject to change without notice.

To avoid the risk of fire and potential injury, product installation must adhere strictly to instructions contained in the Installation and Operation Manual.